

**BTE SLITTING LINE MODEL LIST**

MODEL	THICKNESS(mm)	STRIP WIDTH(mm)	COIL WEIGHT(ton)	LINE SPEED(m/min)
<b>BTE-D 0.3 - 2</b>	0.3 - 2	500	5 - 10 - 15	250
	0.3 - 2	1000	5 - 10 - 15	250
	0.3 - 2	1300	5 - 10 - 15 - 25	225
	0.3 - 2	1600	5 - 10 - 15 - 25	225
	0.3 - 2	1800	5 - 10 - 15 - 25 - 30	200
	0.3 - 2	2000	5 - 10 - 15 - 25 - 30	175
<b>BTE-D 0.3 - 3</b>	0.3 - 3	500	5 - 10 - 15	250
	0.3 - 3	1000	5 - 10 - 15	250
	0.3 - 3	1300	5 - 10 - 15 - 25	225
	0.3 - 3	1600	5 - 10 - 15 - 25	175
	0.3 - 3	1800	5 - 10 - 15 - 25 - 30	175
	0.3 - 3	2000	5 - 10 - 15 - 25 - 30	150
<b>BTE-D 0.4 - 4</b>	0.4 - 4	500	5 - 10	220
	0.4 - 4	1000	5 - 10	220
	0.4 - 4	1300	15 - 25	200
	0.4 - 4	1600	5 - 10 - 15 - 25	175
	0.4 - 4	1800	15 - 25 - 30	175
	0.4 - 4	2000	15 - 25 - 30	150
<b>BTE-D 0.8 - 6</b>	0.8 - 6	500	5 - 10	150
	0.8 - 6	1000	5 - 10	150
	0.8 - 6	1300	15 - 25	150
	0.8 - 6	1600	5 - 10 - 15 - 25	150
	0.8 - 6	1800	15 - 25 - 30	150
	0.8 - 6	2000	15 - 25 - 30	150
<b>BTE-D 1.5 - 8</b>	1.5 - 8	1600	15 - 25 - 30	120
	1.5 - 8	1800	15 - 25 - 30	120
	1.5 - 8	2000	15 - 25 - 30	120
<b>BTE-D 2.5 - 10</b>	2.5 - 10	1600	15 - 25 - 30	100
	2.5 - 10	1800	15 - 25 - 30	100
	2.5 - 10	2000	15 - 25 - 30	100
<b>BTE-D 4 - 12</b>	4 - 12	1600	10 - 15	80
	4 - 12	1800	10 - 15	80
	4 - 12	2000	10 - 15	80